

Travel (mm)	X-axis	710 mm
	Y-axis	450 mm
	Z-axis	460 mm
Distance (mm)	Spindel center to column	514 mm
	Spindel nose to table	150-600 mm
Table	Table (LXW) (mm)	760 x 420 mm(760 x 420)
	Dimesnsion of T-slot (mm)	3(5) x 18 x 100 mm
	Max. table load (kg)	450 kgs
Spindle	Spindle Taper-40	BT/CAT/DIN (HSK Opt.)
	Spindle motor- cont/ 30min (kw)	5.5-7.5 kw
	Belt drive spindle (Taper-40)	8000rpm (10000rpm and 12000rpm Opt.)
	Direct driver spindle (Taper-40)	10000rpm, 12000rpm and 15000rpm Opt.
	Build-in spindle (Taper-40/ HSK-E40/50/63)	20000rpm / 30000rpm Opt.
	Belt drive spindle (Taper-50)	N/A
	Direct driver spindle (Taper-50)	N/A
ATC	ATC-Swing Arm type	24 tools Opt.
	ATC-Chain type	N/A
Feed Rate	Rapid feed rate-X/Y/Z	36/36/32 m/min
	Axis feed motor- X/Y/Z	2.0/2.0/3.0 kw
	Cutting feedrate by table	10 m/min
	X ballscrew (dia. x pitch)	32 x 12mm
	Y ball screw (dia. x pitch)	32 x 12mm
	Z ball screw (dia. x pitch)	32 x 12mm
	Linear guide width (X/Y/Z)	30mmx2 / 35mmx2 / 35mmx2
Machine	Power consumption KVA (Transformer)	25 KVA
	Pneumatic Supplier kg/ cm2	5.5-6.5kg/cm2
	Coolant tank capacity	256 liter
	Floor space requirement	2180 x 2040 cm
	Floor space requirement (with conveyor)	3282 x 2040cm
	Machine weight	4800 kgs

* All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice