

Travel (mm)	X-axis	1500 mm
	Y-axis	700 mm
	Z-axis	650 mm
Distance (mm)	Spindel center to column	730 mm
	Spindel nose to table	150-800 mm
Table	Table (LXW) (mm)	1650 x 700 mm
	Dimesnsion of T-slot (mm)	5 x 18 x 100 mm
	Max. table load (kg)	1000 kgs
Spindle	Spindle Taper-40	BT/CAT/DIN (HSK Opt.)
	Spindle motor- cont/ 30min (kw)	11-15 kw (15-18.5kw Opt.)
	Belt drive spindle (Taper-40)	8000rpm (10000rpm and 12000rpm Opt.)
	Direct driver spindle (Taper-40)	10000rpm, 12000rpm and 15000rpm Opt.
	Build-in spindle (Taper-40/ HSK-E40/50/63)	20000rpm / 30000rpm Opt.
	Belt drive spindle (Taper-50)	6000rpm/ 8000rpm Opt.
	Direct driver spindle (Taper-50)	8000rpm/ 10000rpm Opt.
ATC	ATC-Swing Arm type	24/30 tools Opt.
	ATC-Chain type	32/ 40 tools Opt.
Feed Rate	Rapid feed rate-X/Y/Z	25/25/25 m/min
	Axis feed motor- X/Y/Z	4.0/4.0/4.0 kw
	Cutting feedrate by table	10 m/min
	X ballscrew (dia. x pitch)	50
	Y ball screw (dia. x pitch)	50
	Z ball screw (dia. x pitch)	40
	Linear guide width ( X/Y/Z)	45mmx2 / 45mmx4 / 45mmx2
Machine	Power consumption KVA (Transformer)	45 KVA
	Pneumatic Supplier kg/ cm2	5.5-6.5 kg/cm2
	Coolant tank capacity	560 liter
	Floor space requirement	4150 x 2221 cm
	Floor space requirement (with conveyor)	5131 x 2221 cm
	Machine weight	11000 kgs

\* All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.