

Travel (mm)	X-axis	500 mm
	Y-axis	750 mm
	Z-axis	350 mm
Distance (mm)	Spindel nose to table	150-400 mm
Table	Table (LXW) (mm)	600 x 800 mm
	Dimesnsion of T-slot (mm)	5 x 18 x 125 mm
	Max. table load (kg)	350 kgs
Spindle	Build-in spindle (HSK-E32/E-40/ISO-10)	30000 rpm/40000 rpm/60000 rpm
	Spindle motor- cont/ 30min (kW)	7.5-9 kW
	Spindle cooling	Habor water type closed circuit refrigeration unit width digital control.
ATC	ATC-Genva type (Fully enclosed)	24 tools
	Maximum Tool Length	90 mm
	Maximum Tool Diameter	12 mm
Feed Rate	Rapid feed rate-X/Y/Z	30/30/30 m/min
	Axis feed motor- X/Y/Z	2.0/2.0/2.0 kW
	X ballscrew (dia. x pitch)	32 mm x 10 mm
	Y ball screw (dia. x pitch)	32 mm x 10 mm
	Z ball screw (dia. x pitch)	32 mm x 10 mm
	Linear guide width ( X/Y/Z)	35 x 30 x 35 mm
Machine	Power consumption KVA (Transformer)	25KVA
	Pneumatic Supplier kg/ cm2	5.5-6.5kg/cm2
	Coolant tank capacity	240liter
	Floor space requirement	2200 x 2490 cm
	Floor space requirement (with conveyer)	3300 x 2490 cm
	Machine weight	4000kgs

\* All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.